



MANUFACTURERS TECHNICAL DATA SHEET

KLENZ ENGINE OIL SAE 5W-30 (SN/CF)

Description

TRUSYN® Zero Friction® 5W-30 engine oil provides ultimate engine protection through broader temperature range proficiency. The synthetic base fluid guarantees accurate oil viscosity reducing friction at start-up. **O.E.M. Approved Anti-Wear additive** structure ensures minimum wear in the most sophisticated valve train mechanisms including those with variable valve timing (**VVT**). Optimum power and performance is reached by introducing metallic detergent and ash less dispersant additive system, this provides superior control of ring belt and piston skirt deposits. Specially selected friction modifiers assist in decreasing resistance for maximum fuel economy. **Higher Shear-Stable** formulation provides greater control of oil flow through the ring belt region by maintaining oil viscosity reducing oil evaporation at the elevated ring zone temperatures experienced under all operating conditions.

Application

Suitable for naturally aspirated, fuel injected, turbocharged and multi-valve engines fuelled by **petrol, diesel** or **LPG**.

Advantages / Benefits

TRUSYN® Zero Friction® 5W-30 engine oil extends engine life through broad temperature range proficiency. Superior quality synthetic base oils guarantees correct oil viscosity, reducing friction at start-up, whilst providing effective lubricity during high temperatures. Effective anti-wear additive structure influences outstanding wear control in all sophisticated valve train mechanisms, including those with variable valve timing (**VVT**). Power and performance is preserved through immediate contact with all moving parts creating a protective layer that armors the engine against deposits. Maintenance costs are reduced by higher thermal stability and oxidation resistance minimizing in-service oil degradation thereby eliminating filter obstruction and sludge development. Excellent control of oil flow through the ring belt area is achieved by maintaining oil viscosity.

Performance Standards

TRUSYN® Zero Friction® 5W-30 engine oil meets or exceeds the following Performance Standards

- API SN / CF
- ACEA A3/B3, A3/B4 - 12
- MB 229.3
- VW 502 00 / 505 00
- RN 710/700

Typical Characteristics

Klenz® Pure Protection® Engine Oil SAE 5W30 (SN/CF)

Product Code	KLSYN5W30
API Spec	SN/CF
Base Oil	Synthetic
Colour	Amber / Brown
Appearance	Clear and Bright
Kinematic Viscosity @ 40°C	68 cSt
Kinematic Viscosity @ 100°C	11.6 cSt
Viscosity Index	166
Flash Point	239 °C
Density @ 15°C	Approx.0.850 kg/l
Pour Point	-48 °C

All reasonably practicable steps have been taken to ensure this data sheet and the information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from Klenz Chemicals. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Klenz Chemicals shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. You can contact Klenz Chemicals to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product Name KLENZ TRUSYN 5W-30
Revision 1
Date issued 17 May 2017

Language English