



MANUFACTURERS TECHNICAL DATA SHEET

TRUSYN® Zero Friction® 15W-40 RS-500

Description

TRUSYN® Zero Friction® 15W-40 RS-500 is a premium quality synthetic-blend engine oil that meets the demands of modern passenger cars. **OEM approved** Anti-wear additives along with a blend of superior quality synthetic and group II base oils provide good load bearing properties and protection against wear. Designed for efficient operation in petrol, diesel and gas engines.

Application

Suitable for naturally aspirated, fuel injected, and multi-valve engines fuelled by **petrol, diesel** or **LPG**.

Advantages / Benefits

TRUSYN® Zero Friction® 15W-40 RS-500 is formulated with synthetic base oils which provides excellent oxidation and thermal stability. The use of synthetic base oils results in a finished product that has a high Viscosity Index (VI) ensuring superb cold weather protection whilst providing superior lubricity during high temperatures. Blended using industry-leading **OEM approved** additives for superior wear protection and increased service life.

Performance Standards

TRUSYN® Zero Friction® 15W-40 RS-500 meets the following performance standards :

- API SN / CF
- ACEA A3/B4 - 08
- MB 229.1
- VW 501 01 / 505 00
- PSA B71 2300
- GM-LL-B-025

Typical Characteristics

TRUSYN® Zero Friction® 15W-40 RS-500 (SN/CF)

Product Code	KLSYN15W40
API Spec	SN/CF
Base Oil	Synthetic Blend
Colour	Amber / Brown
Appearance	Clear and Bright
Kinematic Viscosity @ 40°C	107 cSt
Kinematic Viscosity @ 100°C	14.6 cSt
Viscosity Index	140
Flash Point	209 °C
Density @ 15°C	Approx.0.880 kg/l
Pour Point	-15 °C

All reasonably practicable steps have been taken to ensure this data sheet and the information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from Klenz Chemicals. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Klenz Chemicals shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. You can contact Klenz Chemicals to ensure that this document is the most current available. Alteration of this document is strictly prohibited.